



Disassembling Nokia 1110i (RH-93) made in Hongrie

Voila comment démonter ce mobile pour pouvoir le réparer.

Written By: SpOOn3R



INTRODUCTION

This is a disassembly guide for NOKIA 1110i(RH-93).

TOOLS:

- [T6 Torx Screwdriver](#) (1)
 - [Metal Spudger](#) (1)
-

Step 1 — Disassembling Nokia 1110i (RH-93) made in Hongrie



 Switch off the device to avoid shocks while disassembling.

- Turn the device face down and press on the small button at the bottom . Slide the back case down.
- To remove the battery, use your finger to insert it in the groove and pull the battery out.

Step 2



- To remove the protective cover, use the tool shown and press the grey button at the left bottom.
- The front cover ejects as shown. Remove it carefully to avoid damage.
- The keypad case can be removed easily. Pull it up off the device.
- Use a T6 Torx screwdriver to remove the screws.

Step 3



- Find this channel at the top of your device.
- Use a pair of tweezers to remove it carefully without harming the surroundings.
- Insert the spudger into the section to remove the module.

Step 4



- Use the spudger to remove the module casing safely.
- Your device is successfully disassembled.

To reassemble your device, follow these instructions in reverse order.

This document was generated on 2021-07-09 02:10:12 AM (MST).

