

Nobis NB09 Battery Replacement

How to open the Nobis NB09 and gain access to the battery, in order to replace dry or damaged battery.

Written By: Jackson McAdams



INTRODUCTION

This guide will show you how to replace the battery in an Android Nobis NB09 tablet.

Some possible symptoms which could show that your tablet's battery is dying include:

- Battery is at a low percentage even after a fresh charge.
- The tablet dies when it still has a lot of battery life.
- The tablet becomes hot after using for a short period of time.

If you experience any of these symptoms, then it is likely the culprit is a failing battery.



TOOLS:

- Spudger (1)
- iFixit Opening Tools (1)
- 64 Bit Driver Kit (1)
- Soldering Iron (1)

Step 1 — Battery



- A Before beginning this process, make sure the device is powered off.
- Remove the screws holding the case together.

Step 2



Use an opening tool to loosen and pry off the pink back plate.

Step 3





Remove the black electronic tape covering the circuit board.

Step 4



- Use the soldering iron to remove the black and red wires from the circuit board.
- The black wire is the ground and the red wire is the battery positive terminal.
- To reassemble, use the soldering iron to solder the leads at the end of the black (-) and red (+) wires from the new battery onto the proper terminals on the circuit board.

Step 5





- Gently loosen the adhesive under the battery to avoid damaging it.
- Use caution; the battery is soft and will bend very easily.
- (i) Dispose of the old battery properly at an electronic waste center or verified battery recycling store.
- Mhen reassembling, apply adhesive to the back of the new battery.

To reassemble your device, follow these instructions in reverse order.