



iPhone 7 Rear Case Battery Removal

Prereq only for battery removal when replacing...

Written By: Scott Havard



INTRODUCTION

Prereq only for battery removal when replacing the rear case.


TOOLS:

Tweezers (1)

iOpener (1)

Plastic Cards (1)

Step 1 — Rear Case Battery



- Use a pair of tweezers with blunt tips to peel back one of the adhesive strips on the lower edge of the battery.

Step 2



- Use a pair of tweezers with blunt tips to peel back the other adhesive strip on the lower edge of the battery.

Step 3



⚠ Try to keep the strips flat and unwrinkled during this procedure; wrinkled strips will stick together and break instead of pulling out cleanly.

- Slowly pull one battery adhesive tab away from the battery, toward the bottom of the iPhone.
- Pull steadily, maintaining constant tension on the strip until it slips out from between the battery and the rear case. For best results, pull the strip at a 60° angle or less.
- ① The strip will stretch to many times its original length. Continue pulling and re-grab the strip near the battery if necessary.

Step 4



- Repeat the previous step for the second strip.
- ⚠ Hold down the battery as you remove the second strip, or the strip may fling the battery when it separates from the case.
- **If you removed both adhesive strips successfully, skip the next step.**
- Otherwise, if either of the adhesive strips broke off underneath the battery and could not be retrieved, **continue with the next step below.**

Step 5



- ⓘ If you successfully removed both adhesive strips, move on to the next step. Otherwise, you will need to pry the battery from the rear case.
- [Prepare an iOpener](#) and apply it to the back of the rear case, directly over the battery. Alternatively, you can apply heat using a heat gun or hair dryer.
- After about a minute, remove the iOpener, flip the phone over and use a [plastic card](#) to break up any remaining adhesive behind the battery.
- ⚠ Avoid bending the battery. Damage to the battery may release dangerous chemicals, and could start a fire.
- ⚠ Do not pry under the top third of the battery, you may damage the volume button ribbon cable.

Step 6



- Remove the battery from the rear case.
- ★ When installing the battery, refer to [this guide](#) to replace your battery's adhesive strips.

To reassemble your device, follow these instructions in reverse order.